

AIRMATION 2201/789 IC-DS pneumatic motor pump

Ratio 32:1 V - 16 l.p.m.
application: low/medium viscosity products
use: products supply

PUMP PERFORMANCE

Air Inlet Pressure Range	2 - 6 bar
Ratio	32 : 1 B
Max Cycles / Minute	60
Displacement Per Cycle	270 cc
Flow @ 60 Cycles / Minute	16 l.p.m.
Air consumption @ 6 bar	4500 N.l.p.m.

PUMP SPECIFICATIONS

Lower Pump Material	Stainless Steel
Pumping stem material	316 Stainless Steel Hard Chrome opt. 316 SS High Density Ceramic Coated
Cylinder Material	316 L Stainless Steel
Seal set	Teflon/Carbographite spec. compound
Valves balls material	420 SS - opt. Tungsten Carbide
Valves seats material	Tungsten Carbide
Air Motor	2201
Motor Diameter	200 mm
Stroke	150 mm
Air Inlet	G 3/8" (F)
Material Inlet	G 1 1/2" (F)
Material Outlet	G 3/8" (M)

ACCESSORIES:

Air FR+L	DN 3/8"
Wall mount bracket	828025
Delivery filters	198500
Suction filters	196800, 193100, 785

