

AIRMATION 2008/913 IC-D pneumatic motor pump

Ratio 5:1 - 45 l.p.m.

application: low/medium viscosity products

use: pressure supply / transfer / recirculation

PUMP PERFORMANCE

| | |
|---------------------------|---------------|
| Air inlet pressure range | 2 - 6 bar |
| Ratio | 5 : 1 B |
| Max cycles / minute | 60 |
| Displacement per cycle | 757 cc |
| Flow @ 60 cycles / minute | 45 l.p.m. |
| Air consumption @ 6 bar | 1600 N.l.p.m. |

PUMP SPECIFICATIONS

| | |
|-----------------------|-----------------------------------|
| Lower pump material | Stainless Steel |
| Pumping stem material | 316 SS with HDCC ceramic coating |
| Cylinder material | 316 L Stainless Steel |
| Seal set | Teflon + UHMW-PE special compound |
| Air motor | 2008 |
| Motor diameter | 125 mm |
| Stroke | 150 mm |
| Multistage silencer | 2002-35 - Stainless Steel |
| Air inlet | G 3/8" (M) |
| Material inlet | G 1 1/2" (M) |
| Material outlet | G 1 1/2" (M) - opt. G 1" (M) |

ACCESSORIES

| | |
|------------------|---------------------|
| Air FR+L | 3822-CA |
| Mounting bracket | 828025 |
| Delivery filters | 96330, 96430, 97140 |
| Suction filters | 785, 196800 |

